

**Vesmach**

YOUR BAKERY SOLUTIONS PROVIDER

Product Name:

## HORIZONTAL FLOW WRAP PACKING MACHINE

MODEL: SZ-180

Features:

- The whole machine is controlled by three servos;
- Seven-inch touch screen display, easy operation and clear working status;
- Variety of product parameters and formulas can be stored, which can be downloaded and used without repeated settings;
- Automatic adjustment of bag length without manual setting;
- Higher precision and accurate sealing and cutting position;
- Stop position and print position can be set arbitrarily;
- The packaging range is expanded to adapt to a variety of product specifications;
- Reduce the labor intensity of the operator, effectively improve production efficiency.



Purpose:

It is suitable for baking food (moon cake, bread, biscuit, etc), medical equipment, candy, medicine, daily necessities, hardware parts, paper box or tray and other solid and regular packing.

### Specifications

| Model                | 132 (Single Jaw)                              | 132 (Double Jaws) | 90 (Triple Jaws) |
|----------------------|---|-------------------|------------------|
| Package Length       | 120-500 mm                                    | 60-300 mm         | 45-100 mm        |
| Package Width        | 35-160 mm                                     | 35-160 mm         | 35-60 mm         |
| Package Height       | 5-60 mm                                       | 5-60 mm           | 5-30 mm          |
| Packing Speed        | 30-120 bags/min.                              | 30-250 bags/min.  | 30-450 bags/min. |
| Film Size            | 90-400 mm                                     |                   |                  |
| Packaging Film Type  | OPP/CPP, PT/PE, KOP/CPP, VMBOPP, VMCPP, VMPET |                   |                  |
| Type of Power Supply | 220V  |                   |                  |
| General Power        | 3.8 Kw  | 5.3 Kw            | 4.6 Kw           |
| Weight of Machine    | 400 Kg  |                   |                  |
| Dimension            | 4000 X 930 x 1370 mm                          |                   |                  |